Manually changing the status of an imported run deletes comments and evidence without warning, leaving no deletion history except for the status change in the user log.

1 Import a Test Run result using REST API

2 Navigate to that Test Run

3   Move to the Execution Board

TOTAL TESTS: 8

	FAILED	FF	⊞	≣▢
	FAILED	FF	⊞	≣▢
	FAILED	FF	⊞	≣▢
	FAILED	FF	⊞	≣▢
	FAILED	FF	⊞	≣▢
	FAILED	FF	⊞	≣▢

4   Change manually the status, and data will be deleted with no warning.

Online Store
Software project

PLANNING

XSP board
Board ⌄

⧉ Timeline

☰ Backlog

▥ Active sprints

📅 Calendar NEW

📈 Reports

☰ List

◎ Goals

☑ Issues

ⓘ **Keyboard shortcuts**

By pressing SHIFT + → you can move to the next Test.

By pressing SHIFT + ← you can go back to the previous Test.

Execution Status

🔴 FAILED   </> 🟩 ⬜ 🟨 🟧

The test run has passed

Timer

▶ 00:00:00 ↺

No time logged

⌄ **Findings** COMMENT ➕

⌄ **Defects** 0 ➕

None

5 Activity section shows nothing more than the user entry of who changed the status.

ScriptRunner Enhanced ...

Testing Board

Add shortcut

Project settings

resource.CCInput Username

Test details GENERIC

⌄ **Definition**

Login Tests.Invalid Login.CCInvalid Username

› **Activity**

Invite people

You're in a company-managed project

Learn more